

Fan Failure and Temperature Detection Unit (FFTDU)with PT100 SENSOR CMSC – 7933-4/20ma—SHORT CIRCUIT PROTECTED



Fan Failure and Temperature Detection Unit (FFTDU) CMSC – 7933 is an integrated intelligent programmable & compact unit, designed to ensure monitoring of 4 Nos. of **AC impedance protected cooling fans & Capacitor driven FANS & internal panel temperature in a most cost effective and reliable way for FAN currents from 100ma to 450ma.**

When an accidental FAN short circuit place, the INBUILT GLASS CATDRIDGE FUSE FAILS with FF & ROOM TEMPERATURE flashing alternately, with BUZZER ON.

After removing the “SHORT” & replacing the FUSE, the unit works normally.

In CMSC7933 ROOM TEMPERATURE SENSOR IS PT100, TOTALLY REPLACEABLE without any recalibration. CMSC7933 has improved TEMPERATURE MEASUREMENT ACCURACY

- **Wide input Voltage range – 88 VAC – 257 VAC**

It can be connected to non-UPS power source.

- **Programmable Fan voltage (230 VAC / 110 VAC) with in-built protection fan protection.**

CMSC-7933 can be programmed to control fans with 230 VAC input voltage as well as 110VAC input voltage. CMSC-7933 also protects 110VAC fans by switching off the output voltage to the fans if 230VAC input voltage is connected inadvertently.

- **Auto-characterizing of individual AC fans**

In the data sheet of AC Impedance protected fans, the input current values specified are with a tolerance of 10%-20% depending of the manufacturer and the batch of production. Also, AC impedance protected fans have minimal difference between stall current and nominal current. Therefore, Century Make CMSC-7933 offers unique feature of auto-characterization of each fan input current, thus eliminates the need for entering the current rating of each cooling fan motor.

- **Individual control of cooling fans (4 Relay Output)**

CMSC-7933 is versatile can be programmed for use with 1 No. to 4 No. of cooling fans. Thus CMSC-7933 reduces to requirement of maintaining inventory of different types of FTDDU's.

- **Programmable fan operating condition**

CMSC-7933 can be programmed to ensure operation of cooling fans in most cost effective manner, the unit can be programmed to switch on cooling fans, if the ambient temperature is higher than the desired ambient temperature of PLC/DSC panels. Thus it reduces to operating costs and provides longer operating life for the AC impedance protected cooling fans.

- **Continuous Evaluation of cooling fan motors**

The cooling fans motor current also varies given the input voltage variation. CMSC-7933 intelligent program monitors current drawn by individual fan motors with respect to input voltage variation and thus identifies fan stall condition independent of input voltage variations. CMSC-7933 checks fan motor status every 60 seconds to ensure quick diagnosis of fan motor status.


- **Ease of interfacing with supervisory control system with programmable output status (NO / NC contact)**

1 No. for potential free relay output for over temperature indication

1 No. of Potential free relay output for fan failure condition (OPEN / STALL)

- **User friendly interface for Easy programming**

Temperature set values, functional parameters & operating values of CMSC-7933 can be easily programmed through Four Nos of capacitive touch sensitive keys (Increase – Decrease – Scroll – Enter) & 3 Digit seven segment LED display.



CENTURY METERING SYSTEMS & CONTROLS

#34 1B, 1st Floor, 4th main,
3rd phase Peenya Industrial Area,
Bangalore – 560 058

Phone : 080-29371315 & 16

e-mail: century.metering@gmail.com

www.centurymetering.in

Fan Failure and Temperature Detection Unit (FFTDU) with PT100 SENSOR CMSC – 7933-4/20ma—SHORT CIRCUIT PROTECTED

- **In-built User Operational safety**

CMSC-7933 is designed with assured galvanic isolation of user interface in case of interchange of phase & neutral at the input.

- **For Quick Diagnosis of fan status**

6 No. of red LED indicators

4 Nos. of LED indicates status of each cooling fan

1 No. of LED indicator for fan STALL status, which is common for all 4 fans.

1 No. of LED indicator for fan OPEN status, which is common for all 4 fans.

- **Ambient Temperature Measurement**

FFTDU CMSC-7933 has integrated temperature sensor and unique mechanical design of enclosure & mounting location ensure reliable measurement of internal temperature of PLC/DCS panels. Optional isolated 4-20mA signal (output impedance of 500Ω) provides easy connection with supervisory control system over long distance.

- **For Quick Diagnosis of temperature status**

1 No. of RED LED indicator for High Temperature Alarm

1 No. of GREEN LED Indicator for Normal Temperature condition (Fan running Condition)

1 No. of Yellow LED indicator for ambient temperature lower than set value.

- **Audio Alarm for quick response**


Buzzer for over-temperature annunciation.

- **Easy of Mounting**

CMSC-7933 has compact size (45mm X 78mm X 180 mm - excluding DIN rail mount) Mounted on standard DIN Rail Profile weighing less than 600 gms provides ease of installation at any location in the PLC/DCS panels.

Technical Specifications

Operating Voltage	:	88 V to 257 V.
Operating Temperature Range	:	0 to 85 deg C
Input / Output terminals	:	Screw connections with Plug-in terminal blocks
Ambient Temperature	:	0 – 70 deg.C.
Ambient Humidity	:	0 – 90% Relative Humidity (non-condensing)
Fan Current	:	100mA TO 450mA
Types of Fans	:	Both Impedance protected & Capacitor driven fans
Temperature Measurement Accuracy		
		With Semiconductor Sensor
Range		0 to 70 deg C
Accuracy		+/- 0.5 deg C
Optional Output Temperature signal Specifications		
Range	:	4 to 20 mA
Signal accuracy	:	+/- 0.5 %
Maximum Load Resistance	:	500 Ohms



CENTURY METERING SYSTEMS & CONTROLS

#34 1B, 1st Floor, 4th main,
3rd phase Peenya Industrial Area,
Bangalore – 560 058

Phone : 080-29371315 & 16


e-mail: century.metering@gmail.com

www.centurymetering.in

**Fan Failure and Temperature Detection Unit (FFTDU)with PT100 SENSOR
CMSC – 7933-4/20ma—SHORT CIRCUIT PROTECTED**

Ordering Information

Model No:	Description
CMSC 7773-S	With Semiconductor Temperature sensor & Without 4-20mA O/P
CMSC 7773-S-4-20mA	With Semiconductor Temperature sensor & with 4-20mA O/P
CMSC 7773-S-RoHs	With Semiconductor Temp. Measurement & Without 4-20mA O/P
CMSC 7773-S-RoHs/4-20mA	With Semiconductor Temp. Measurement & 4-20mA O/P
CMSC 7908 – MODBUS	With MODBUS and Semiconductor Temperature sensor
CMSC 7913	With Semiconductor Temperature sensor, Without Stall & Without 4-20mA O/P
CMSC 7913/4-20mA	With Semiconductor Temperature sensor, Without Stall & with 4-20mA O/P
CMSC 7913 - MODBUS	With Semiconductor Temperature sensor, Without Stall & Without 4-20mA O/P
CMSC 7916 – DC	With Semiconductor Temperature sensor, With Stall
CMSC 7795 – DC	Without Display, Without Semiconductor Temperature, With Stall
CMSC 7933	SEMICONDUCTOR SENSOR & SHORT CIRCUIT PROTECTION & Without 4-20mA O/P
CMSC 7933-4-20mA	SEMICONDUCTOR SENSOR & SHORT CIRCUIT PROTECTION With 4-20mA O/P



CENTURY METERING SYSTEMS & CONTROLS

#34 1B, 1st Floor, 4th main,
3rd phase Peenya Industrial Area,
Bangalore – 560 058

Phone : 080-29371315 & 16
e-mail: century.metering@gmail.com
www.centurymetering.in